

# RG80-SDUC

70x70

## ► The most advanced packaging solution

Step into the market with a **BESPOKE TURNKEY SOLUTION!**

What are the ingredients that make the RG80 the most advanced packaging solution for liquid and viscous food products?

- **UTMOST PRODUCT CARE:** the **nutritional and organoleptic properties** of the packaged products are preserved and the quality of the end product is significantly higher compared to other packaging systems.
- **OUTSTANDING HYGIENIC PERFORMANCE:** thanks to our design solutions, the product is packed **avoiding re-contamination** and **package integrity** is ensured throughout its whole shelf life.
- **COMPETITIVE INVESTMENT:** **good value for money** and **low running costs** make the RG80 more competitive than other packaging systems.
- **VERSATILITY:** the DDF dosing unit allows to fill products **containing particles or with different viscosity grades** while maintaining top production efficiency levels. Our filling machines are **flexible** and allow for switching to **different volumes** in less than **3 minutes**.
- **EASE OF USE AND MAINTENANCE:** the RG80 is designed to be **intuitive** and to make the work of operators and maintenance technicians **faster** and **more efficient**.

GALDI's automatic filling machine model **RG80-SDUC** is designed for the forming, filling and sealing of Gable Top paperboard cartons in the **STANDARD cross section**, with **Ultra Clean System**.

The machine is suitable for the filling of **ESL milk, fresh milk, cream, drinking yoghurt, fruit juice, liquid egg and other liquid food products**.

**Available fill sizes:** 1000 ml – 750 ml – 500 ml – 330 ml – 250 ml



In line with our continuous improvement policy, all specifications are subject to change without notice. Illustrations, descriptions and technical specifications are not binding and may change.

Via E. Fermi, 43/B  
31038 Paese (TV) ITALY  
Ph. +39 0422 482211  
info@galdi.it  
www.galdi.it

follow us



# RG80-SDUC

70x70

## ► Machine Specifications

### Standard Features:

- Double Wall Insulated Product Balance Tank
- Modulating System for Product Inlet
- Automatic CIP Box Cover
- DDF Dosing Unit with Bottom-Up System
- Carton Disinfection System (35% H<sub>2</sub>O<sub>2</sub>)
- Drainable Machine Bed
- Recovery Pump
- IFCM Sanitizing system
- Digital native machine: next-gen diagnostics ready, with advanced sensors for data collection and analysis

### Available Options:

- Rotary Screw Cap Applicator Single Index Servomotor Driven
- External Foam Cleaning System
- Sterile Air System for Product Tank and Filling Chamber
- Ejection System for Rejected Cartons
- Independent Cleaning Unit Self-CIP
- CIP Box Quick Rinse Phase

## ► Technical Features

<b>Maximum rated mechanical speed*</b>	Up to 3500 cartons/hour	
<b>Cross section</b>	70x70 mm	
<b>Fill sizes</b>	From 250 ml to 1150 ml	
<b>Machine dimensions</b>	L 6100 x W 2770 x H 3360 mm	
<b>Filler</b>	Double Diaphragm Filler with Bottom-Up System	
<b>Electrical data</b>	Maximum Power	39 kW
	Nominal Power	21 kW
	Nominal Voltage	400 Vac +/-10% - 50 Hz
	No. of Phases	3P + N + E
<b>Compressed air</b>	Flow	520 nl/min
	Pressure	600 kPa
<b>Cooling water</b>	Chilled water	5,5 l/min @ 4 °C - 400 kPa

\*Production speed varies according to product and carton characteristics

In line with our continuous improvement policy, all specifications are subject to change without notice.  
Illustrations, descriptions and technical specifications are not binding and may change.